

# PRODUCT SPECIFICATIONS

## Adapter Faceplate

### INTRODUCTION

LUX offers a wide range of fiber adapter plate for various applications such as Rack Mount Enclosure & Wall Mount Distribution box. These adapters plates are designed with snap-in for easy & quick installation.

These adapter faceplates are available with an option of E2000, FC, LC, SC & ST adapter and also a selection of Single-mode (OS1/OS2) and Multi-mode (OM1/OM2/OM3/OM4).



### TECHNICAL INFORMATION

<b>Max. Capacity</b>	24port – LC 12port – FC / SC / ST
<b>Dimension</b>	32mm (H) x 155 mm (W) x 2mm (D)
<b>Material</b>	Steel
<b>Color</b>	Black (RAL 9004) Grey (RAL 7035)
<b>Durability</b>	500 times $\Delta \leq 0.2\text{dB}$

### ENVIRONMENTAL PROPERTIES

<b>Storage and shipment temperature:</b>	- 20°C to 70°C
<b>Operating and Installation temperature:</b>	- 20°C to 70°C
<b>Restriction of Hazardous Substances (RoHS) Compliance:</b>	All materials & components meet the requirements of Directive 2002/95/EC.

### ORDERING PART NUMBER

Example: FAP-SMFC12BL = 12 Port FC Singlemode Faceplate (Black)

<b>Character</b>	F	A	P	-	A	B	C	D	E	F	G	H
<b>Example</b>	F	A	P	-	1	2	F	C	S	M	B	L

#### AB – Fiber Count

04 = 4 Fibers  
06 = 6 Fibers  
08 = 8 Fibers  
12 = 12 Fibers  
24 = 24 Fibers\*

#### CD – Adapter Type

E2 = E2000  
FC = FC  
LC = LC  
SC = SC  
ST = ST

#### EF – Fiber Type

M1 = OM1  
M2 = OM2  
M3 = OM3  
M4 = OM4  
SM = SM (OS1/OS2)

#### GH – Color of Faceplate

BL = Black  
GY = Grey

\*\*\*24 F is only available with LC adapter