

PRODUCT SPECIFICATION

ADAPTER FACEPLATE

INTRODUCTION

LUX offers a wide range of fiber adapter plate for various applications such as Rack Mount Enclosure & Wall Mount Distribution box. These adapters plates are with snap-in mechanism for easy & quick installation.

These adapter faceplates are available in FC, LC, SC & ST adapters with Singlemode & Multimode fiber.



TECHNICAL INFORMATION

Max. Capacity	24port – LC 12port – FC / SC / ST
Dimension	S-Type: 32mm (H) x 155 mm (W) x 2mm (D) L-Type: 38mm (H) x 188 mm (W) x 2mm (D)
Material	Steel
Color	Black (RAL 9004) Grey (RAL 7035)
Durability	500 times $\Delta \leq 0.2$ dB

ENVIRONMENTAL PROPERTIES

Storage and shipment temperature:	- 20°C to 70°C
Operating and Installation temperature:	- 20°C to 70°C

REFERENCE STANDARDS

Restriction of Hazardous Substances (RoHS) Compliance:	All materials & components meet the requirements of Directive 2002/95/EC.
---	---

ORDERING PART NUMBER

Example: FAP-12FCSM-S-1-B = 12port FC SM Adapter Plate (1-12) Black - S Type

Character	F	A	P	-	A	B	C	D	E	F	-	G	H	-	I
Example	F	A	P	-	1	2	F	C	S	M	-	S	1	-	B

AB – FIBER COUNT	CD - ADAPTER TYPE	EF – FIBER TYPE	G –TYPE	H – NUMBERING	I – COLOR
08 = 8 Fiber 12 = 12 Fiber 24 = 24 Fiber (LC Only)	FC = FC LC = LC SC = SC ST = ST	SA = Singlemode APC SM = Singlemode MM = Multimode	S = S-TYPE L = L-TYPE	1 = 1-12 4 = 13-24 / 1-24 (LC only) 8 = 25-48 (LC only)	B = BLACK G = GREY

The information and specification in this document are subjected to change without notice