

PRODUCT SPECIFICATION

INDOOR WALL MOUNT DISTRIBUTION BOX

INTRODUCTION

LUX's Indoor Wall Mount Distribution Boxes are designed for terminating, splicing and interconnecting up to 48 fiber optical cables with FC/SC/ST connectors, or a maximum of 96 fiber with LC connectors.

LUX also offers a small wall mount distribution box which is compact in size dedicating for limited installation space require.



TECHNICAL INFORMATION

Max. Capacity Size 1: 96 port (LC) or 48 port (FC/SC/ST)
Size 2: 48 port (LC) or 24 port (FC/SC/ST)

Dimension Size 1: 325(H) x 325(W) x 85(D) mm
Size 2: 260(H) x 300(W) x 85(D) mm

Material Steel

Color Grey (RAL 7035) / Black (RAL 9004)

Accessories Screws / Velcro Straps / 24 fiber splice tray

FEATURES & BENEFITS

- Quick & Easy installation
- Compact in size
- FC/LC/SC/ST available for option
- Security lock

ENVIRONMENTAL PROPERTIES

Storage and shipment temperature: - 20°C to 70°C

Operating and Installation temperature: - 20°C to 70°C

Restriction of Hazardous Substances (RoHS) Compliance: All materials & components meet the requirements of Directive 2002/95/EC.

ORDERING PART NUMBER

Example: IWM-S12FCSM-B = 12port FC SM Wall Mount Indoor Distribution Box (Black)

Character **I** **W** **M** - **A** **B** **C** **D** **E** **F** **G** - **H**

Example **I** **W** **M** - **S** **1** **2** **F** **C** **S** **M** - **B**

A – SIZE	BC – CAPACITY	DE – CONNECTOR TYPE	FG – FIBER TYPE	H – COLOR
L = Size 1 S = Size 2	12 = 12 port 24 = 24 port 48 = 48 port 96 = 96 port	FC = FC LC = LC SC = SC ST = ST	SA = Singlemode APC SM = Singlemode MM = Multimode	B = Black G = Grey

The information and specification in this document are subjected to change without notice