



COMMUNICATIONS

Let's Get Connected

PRODUCT SPECIFICATION

OUTDOOR WALL MOUNT DISTRIBUTION BOX

INTRODUCTION

LUX's Outdoor Wall Mount Distribution Box is designed for terminating, splicing and interconnecting up to 96 fiber optical cables with FC/SC/ST connectors or 192 fiber with LC connector in outdoor environment.

The terminal can be adapted to applications by mounting the enclosure to the exterior surface and connecting between the distribution and drops.



TECHNICAL INFORMATION

Max. Capacity Size 1: 192 port (LC) or 96 port (FC/SC/ST)
Size 2: 48 port (LC) or 24 port (FC/SC/ST)
Size 3: 24 port (LC) or 12 port (FC/SC/ST)

Dimension Size 1: 400(H) x 500(W) x 200(D) mm
Size 2: 300 (H) x 400(W) x 100(D) mm
Size 3: 200 (H) x 230(W) x 58(D) mm

Material Steel

Color Grey (RAL 7035) / Black (RAL 9004)

Accessories Screw / Velcro Strap / Splice tray

ENVIRONMENTAL PROPERTIES

Storage and shipment temperature: - 20°C to 70°C

Operating and Installation temperature: - 20°C to 70°C

Restriction of Hazardous Substances (RoHS) Compliance: All materials & components meet the requirements of Directive 2002/95/EC.

FEATURES & BENEFITS

- Quick & Easy installation
- IP 65 Rated
- FC/LC/SC/ST available for option
- Security lock

ORDERING PART NUMBER

Example: FIPWMA-12-FC-GY-S = 12port FC SM IP65 Outdoor Wall Mount Distribution Box (Grey Size 3)

Character	F	I	P	W	M	A	-	A	B	-	C	D	-	E	F	-	G
Example	F	I	P	W	M	A	-	1	2	-	F	C	-	G	Y	-	S

AB - CAPACITY

ZZ = Empty
12 = 12 port
24 = 24 port
48 = 48 port
96 = 96 port
H4 = 144 port
H9 = 192 port

CD - ADAPTER TYPE

FC = FC
LC = LC
SC = SC
ST = ST

EF - COLOR

GY = Grey
BL = Black

GH - SIZE

L = Size 1 (Max: 96port FC/SC/ST)
M = Size 2 (Max: 24port FC/SC/ST)
S = Size 3 (Max: 12port FC/SC/ST)

The information and specification in this document are subjected to change without notice