LUX COMMUNICATIONS
Let's Get Connected

PRODUCT SPECIFICATION
MPO PATCH PANEL

INTRODUCTION

LUX's MPO patch panel is a high-density panel especially designed for accommodating high-density cabling solution in Data Center and Telecommunication central office.

LUX's MPO patch panel supports maximum 4 x MPO cassettes in 1U, 8 x cassettes in 2 x 1U and 16 cassettes in 4 x 1U. Each MPO cassette is available in 12 or 24 x LC connectors, which provides the maximum of 96 ports in 1U, 192 ports in 2 x 1U and 384 ports in 4 x 1U (LC).

TECHNICAL INFORMATION

Max. Capacity	96 port LC (1U, 4 slots)
Dimension:	1U: 44mm (H) x 482mm (W) x 370mm (D)
Material	Steel
Color	Black (RAL 9004)
Accessories	Screws / Velcro straps / Identification label / Side Cable Management (Optional)

FEATURES & BENEFITS

- Quick & Easy installation to save time
- Up to 50% space saving due to high density
- Improve fiber patch cable management

ENVIRONMENTAL PROPERTIES

Storage and shipment temperature:	- 20°C to 70°C
Operating and Installation temperature:	- 10°C to 60°C
Restriction of Hazardous Substances (RoHS) Compliance:	All materials & components meet the requirements of Directive 2002/95/EC.

ORDERING PART NUMBER

Example: MPP-1UBLN = 1U 4 slots MPO Patch Panel (Black) without rear cable management

Character	M	P	P	–	A	B	C	D	E
Example	M	P	P	–	1	U	B	L	N

AB – HEIGHT (U)	CD – COLOR	EF – SIDE CABLE MANAGEMENT
1U = 1U, 4 slots	BL = Black	N = Not Applicable Y = with side cable management

The information and specification in this document are subjected to change without notice