


PRODUCT SPECIFICATION

FIBER PATCH PANEL (LC/SC)

INTRODUCTION

LUX's fiber patch panel supports maximum fiber splicing up to 48 port LC adapter or 24 port SC adapters in 1U. This fiber patch panel is sliding type, which slides out approx. 20cm with factory made port marking and Knurled screw locking mechanism.

Adjustable mounting brackets allows the panel move inward to the rack up to 55mm.



TECHNICAL INFORMATION


Max. Capacity	48port – LC (24 x LC Duplex) 24port – SC
Dimension	40mm (H) x 435mm (W) x 235mm (D)
Material	Steel (Powder coated)
Color	Black (RAL 9004)
Accessories	4 x 12F Splice holders / 8 x Cable coils / 2 x AG-20S Cable Glands (Black) / 48 x Splice sleeves

ENVIRONMENTAL PROPERTIES

Storage and shipment temperature:	- 20°C to 70°C
Operating and Installation temperature:	- 20°C to 70°C
Restriction of Hazardous Substances (RoHS) Compliance:	All materials & components meet the requirements of Directive 2002/95/EC.

ORDERING PART NUMBER

Example: FP1-1U24LCM3 = 1U 24 port LC OM3 Patch Panel



The information and specification in this document are subjected to change without notice